




Specification

Datum : 25.9.06


Type : RK 356/2

Turns ratio :	1 : 2,3
Achievement:	
Prim. Source impedance :	1 Ohm
Sec. Load impedance :	300 Ohm
Max. input level:	
Sec. Level:	22 dBu
Frequency range:	40Hz - 20KHz +/- 0,3dB
Total harmonic distortion:	0,3% to 40Hz
Common-mode rejection ratio:	
Common-mode rejection ratio (IEC) :	> 40dB 15KHz
Output impedance (primary shorted) :	< 40 Ohm 15KHz
Impedance :	6 Kohm 1KHz 1 - 2
Inductance :	
DC-Bias :	
Coil resistance:	1 - 2 = 3 Ohm ; 3 - 6 = 12 Ohm
Isolation resistance :	
Physical dimensions max :	43 x 26

Drawing .



Pinning : bottom view



Werkstätte für Studio-Technik Dipl.-Ing. H. Haufe

61250 Usingen - Weilburger Strasse 14 - Telefon (06081) 9153-0 Telefax (06081) 9153-20 Mail: haufe.metall@gmx.de
Werk 2 - 08340 Beierfeld - August-Bebel-Strasse 131 - Telefon (03774) 62116 - Telefax (03774) 62117 Mail: haufe.metall@gmx.de